# LITHIUM CELL TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name/Description of cell / modeln o. of Product		
	e.g. TX-120	
	Manufacturer of cell	
Name	Dongguan Bettercell Technology Co.,Ltd	
Address	A2 Building , Fenghuangguang Road No.80, Fenghuanggang Village, Tangxia	
	Town ,Dongguan City ,China	
Phone	0769-86050699	
E-Mail	<u>294414503@qq.com</u>	
Website	www.better-cell.com	
	Manufacturer	

Name	Technaxx Deutschland GmbH & Co. KG	
Address	Kruppstraße 105, 60388 Frankfurt am Main	
Phone	+49 [69] 90 47552 0	
E-Mail	Zentrale@technaxx.de	
Website	http://www.technaxx.de/	
	Test laboratory of cell	

Name	Shenzhen CCJC Technology Co., Ltd
Address	1st Floor, Xinbaoyi Industry and Trade Building B, Houting Community, Shajing Town, Bao'an District, Shenzhen City, Guangdong China
Phone	(86-755)23707853
E-Mail	sales @ ccjctek.com
Website	www.ccjctek.com

#### **ID-number and date**

Unique test report identification number	CCJC2019A3400
Date of test report	2019-12-20
DESCRIPTION OF CEL	L ( Mark with an"X")
Lithium ion cell	X
Lithium metal cell	
Paran	neters
Mass in gram (g):	215g
Lithium ion: Indicate watt-hour rating (Wh):	41.07Wh
Lithium metal: Indicate lithium metal content in gram (g):	N/A

### Physical description of cell

#### **Model numbers**

PLG7843126

#### **TESTS AND RESULTS**

List of tests conducted and results	N/A	Pass	Fail
- Mark N/A, pass or fail with an "X"			
T1 - Altitude simulation		X	
T2 - Thermal Test		X	
T3 – Vibration		X	
T4 – Shock		X	
T5 - External Short Circuit		X	
T6 - Impact - for cylindrical cells having a diameter of at least 18 mm	X		
T6 - Crush - for prismatic cells, pouch cells, button cells and cylindrical cells		X	
having a diameter of less than 18 mm			
T7 – Overcharge		X	
T8 - Forced Discharge		X	

# ADDITIONAL SUPPLIER INQUIRY

Mark Yes or no with an "X"		No
Quality management system for manufacturing cells		
Does the manufacturer of the cell/battery manufacture the products based on a		
documented quality management system according to transport regulations?		
Are the following parameters exceeded?		X
Lithium ion cell: more than 20 Wh		
Lithium metal cell: more than 1 g Lithium		

## Check point 13 – 15 need to be answered when 12 has been ticked "YES":

Mark Yes or no with an "X"	Yes	No
Does each cell incorporates a safety venting device or is designed X		
to preclude a violent rupture under normal conditions of carriage?		
Is each cell equipped with an effective means of preventing external short circuits?	X	
Is each battery containing cells or series of cells connected in parallel	X	
equipped with effective means as necessary to prevent dangerous reverse		
current flow (e.g. diodes, fuses, etc.) Not relevant for cells		

 Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion cells and lithium polymer cells

 State of Charge (SoC) max. 30 %
 X

## CELLS INSTALLED IN EQUIPMENT

Check point 17 needs to be answered when the cells are installed in articles: Mark	N/A	Pass	Fail
N/A, pass or fail with an "X"			
17c) Only button cells enclosed?			
17b) Number of enclosed cells (other than button cells) per equipment			
When the equipment is intentionally active/switched on during transport e.g. data logge	rs:		
17c) Confirmation that no dangerous amount of heat is emitted from the equipment		X	
17d)Confirmation that the equipment when transported by air fulfills the defined air		X	
transport standards for electromagnetic radiation according to DO-160			

Please markt he correct column with	an X	
Single Cell or Battery	Build in Cell/ Battery	Over 100Wh
LITHIUM - METALL With the second sec	LITHIUM - IONEN UN 3481 UN 3481 Zelle / Batterie in Ausrüstungen	LITHIUM - IONEN BATTERIE mit MEHR als 100 Wh

Place, Date	CEO Pascal Pekcan	Company stamp
Frankfurt 19.12.2019	Pull	Technaxx Deutschland GmbH & Co. KG Kruppstr. 105 60388 Frankfurt a.M. <sub>Fon +49006080</sub> 47 55 2-0 - Fax-16