Technaxx[®] * Original operating instructions Technaxx Battery air compressor TX-157

Declaration of Conformity: **www.technaxx.de/** (in bottom bar "Konformitätserklärung"). Before using the device the first time, please read the user manual carefully.

Service phone No. for technical support: **01805 012643** (14 cent/minute from German fixed-line and 42 cent/minute from mobile networks). Free Email: **support@technaxx.de**

Keep this user manual for future reference or product sharing carefully. Do the same with the original accessories for this product. In case of warranty, please contact the dealer or the store where you bought this product.

Warranty 2 years

Features

- •6000mA Li Ion battery for up to 4 car tires (2,0-2,4bar)
- •up to 8 bar maximum pressure
- Work lamp with 6 LEDs
- •4 adapters for all valve types
- Aluminium housing
- •Large display for setting/reading the pressure
- •4 pressure units selectable (PSI, BAR, KPA, KG/CM²)
- •Storage bag made of EVA material

Installation and use



1.adjust the pressure hose and connect to tire valve2.Select the pressure unit3.Set the pressure, e.g. 2,3bar4.Start inflating

•Connect the Technaxx Battery air compressor TX-157 with one of the charging cables and load the item fully. The normal charging time is 4 hours Connect one end of the tire inflation joint to the air cylinder and the other end to the tire valve, use correct adapter type. • Note that the order of the connections is important; at the same time, note that there are two types of adapters, American and French. When the power button is pressed, the LCD display start

Press again to start select one of the four units of PSI, BAR, KAP, KG/CM. ●Select the unit you want, set the button to set the air pressure value you need, and finally press the power button. •The compressor starts.• The setting button adjust the pressure the pressure value flashes for 4 seconds, is automatically set, or can be set by pressing the switch. • Press the power switch, when the inflation pressure reaches the pressure value you set, the smart air cylinder will automatically stop, but the LED light is still on, then press the power switch to turn off the light. When the inflation is over, the tire inflation joint is quickly unscrewed from the valve core or the counterclockwise. Before the screwing out, Attention, some parts could be hot. If there is a small leak in the moment of screwing out the joint, it is normal.

Тор					
1.	Pressure Display	4.	Setting button		
2.	On/off	5.	Charging ports		
3.	Battery Level	6.	Power and LED button		

Product overview

Technical specifications

Input voltage	DC 12V (cigarette lighter socket)
Power consumption	12V max. 3A
Input USB	5V max. 2A
Working temperature	–10°C ~ 45°C
Storage temperature	5°C ~ 30°C
Material	Aluminium
Weight / Dimensions	750g / (L) 28,9 x (Ø) 7,3cm
Package contents	TX-157, User Manual, Connection cable for the cigarette lighter and USB Kabel, 4 adapters for all valve types

Warnings

●Danger! - Read the operating instructions to reduce the risk of injury ●Caution! Wear ear-muff s. The impact of noise can cause damage to hearing ●Beware of hot parts! ●Inspect the equipment and accessories for transport damage. ●The equipment and packaging material are not toys. ●Do not let children play with plastic bags, foils or small parts. There is a danger of swallowing or suffocating! ●Please note that our equipment has not been designed for use in commercial, trade or industrial applications. Our warranty will be voided if the machine is used in commercial, trade or industrial businesses or for equivalent purposes.

•The electric power tool generates an electromagnetic field during operation. Under certain circumstances this field may actively or passively impede medical implants. To reduce the risk of serious or fatal injuries, we recommend persons with medical implants to consult their doctor and the manufacturer of the medical implant prior to using the equipment. •When using the equipment to inflate objects, check the information and safety instructions provided by the manufacturer. •Keep all safety devices, air vents and the motor housing free of dirt and dust as far as possible. Wipe the equipment with a clean cloth or blow it with compressed air at low pressure. •Do not squeeze, collide or pull the power cord hard to avoid damage to electronic parts. • Do not attempt to disassemble, it may result in short-circuit or even damage. ● Do not drop or shake, it may break internal circuit boards or mechanics. • Do not expose to rain or moisture, dripping or splashing, to reduce the risk of fire or electrical shock. • Keep device ventilated the in dry and environment, avoid high humidity/temperature. ● Do not install the device near any heat source (e.g. radiators, oven) and keep it away from direct sunlight. ● Keep the device away from little children.



Hints for Environment Protection: Packages materials are raw materials and can be recycled. Do not disposal old devices or batteries into the domestic waste. **Cleaning:** Protect the device from contamination and pollution (use a clean drapery). Avoid using rough, coarse-grained materials or solvents/aggressive cleaner. Wipe the cleaned device accurately. **Distributor:** Technaxx Deutschland GmbH & Co.KG, Kruppstr. 105, 60388 Frankfurt a.M., Germany

Enjoy your product * Share your experience on one of the well known internet portals.