LITHIUM CELL TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

	Name/Description of cell / mo				
Li-ion Battery	L.	FMT1000BT / FMT	2000BT		
		acturer of cell			
Name		Dongguan Golden Cel Battery Co., Ltd.			
Address		No.11, Yinhu Industrial park, JiaoYiTang Management Zone, TangXia,			
	DongGuan, GuangDong, China				
Phone	+86-0769-82195308				
E-Mail	zhirongjian@qq.com				
Website					
NI		nufacturer			
Name	Technaxx Deutschland GmbH & C				
Address	Kruppstraße 105, 60388 Frankfur	am iviain			
Phone	+49 [69] 90 47552 0 Zentrale@technaxx.de				
E-Mail	http://www.technaxx.de/				
Website		oratory of cell			
Name		-			
Address		Shenzhen TCT Testing Technology Co., Ltd. 1F, Building 1, Yibaolai Industrial Park, Qiaotou Village, Fuyong Town,			
Address			illage, Fuyong	rown,	
Phone	+86-755-83392668	Baoan District, Shenzhen, Guangdong, China			
E-Mail	100 700 00002000				
Website					
· · · · · · · · · · · · · · · · · · ·	ID-nun	ber and date			
Unique test report i	dentification number	TCT160316	M012		
Date of test report			2016-03-22		
· · · · · · · · · · · · · · · · · · ·	DESCRIPTION OF	CELL (Mark with an			
Lithium ion cell		X	-		
Lithium metal cell					
	Pa	rameters			
Mass in gram (g):		16.2			
Lithium ion: Indicat	e watt-hour rating (Wh):	2.96			
Lithium metal: India	cate lithium metal content in gram (g):				
	Physical d	escription of cell			
Li-ion battery		F			
430929	Mod	el numbers			
730323					
	TESTS A	AND RESULTS			
List of tests conduc	ted and results		N/A	Pass	Fa
- Mark N/A, pass or	fail with an "X"				
T1 - Altitude simulat	tion			Х	

List of tests conducted and results		Pass	Fail
- Mark N/A, pass or fail with an "X"			
T1 - Altitude simulation		Х	
T2 - Thermal Test		Х	
T3 – Vibration		Х	
T4 – Shock		Х	
T5 - External Short Circuit		Х	
T6 - Impact - for cylindrical cells having a diameter of at least 18 mm		Х	
T6 - Crush - for prismatic cells, pouch cells, button cells and cylindrical cells		Х	
having a diameter of less than 18 mm			
T7 – Overcharge		х	
T8 - Forced Discharge		Х	

ADDITIONAL SUPPLIER INQUIRY

Mark Yes or no with an "X"	Yes	No
Quality management system for manufacturing cells	Х	
Does the manufacturer of the cell/battery manufacture the products based on a		
documented quality management system according to transport regulations?		
Are the following parameters exceeded?		Х
Lithium ion cell: more than 20 Wh		
Lithium metal cell: more than 1 g Lithium		

Check point 13 – 15 need to be answered when 12 has been ticked "YES":

Mark Yes or no with an "X"	Yes	No
Does each cell incorporates a safety venting device or is designed	X	
to preclude a violent rupture under normal conditions of carriage?		
Is each cell equipped with an effective means of preventing external short circuits?	Х	
each battery containing cells or series of cells connected in parallel		
equipped with effective means as necessary to prevent dangerous reverse		
current flow (e.g. diodes, fuses, etc.) Not relevant for cells		

Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion cells and lithium polymer cells

|--|

CELLS INSTALLED IN EQUIPMENT

Check point 17 needs to be answered when the cells are installed in articles: Mark	N/A	Pass	Fail
N/A, pass or fail with an "X"			
17c) Only button cells enclosed?		Х	
17b) Number of enclosed cells (other than button cells) per equipment			
When the equipment is intentionally active/switched on during transport e.g. data logge	ers:		
17c) Confirmation that no dangerous amount of heat is emitted from the equipment		Х	
17d)Confirmation that the equipment when transported by air fulfills the defined air		Х	
transport standards for electromagnetic radiation according to DO-160			

	X	
Single Cell or Battery	Build in Cell/ Battery	Over 100Wh
LITHIUM - METALL UN 3090 Einzel Zelle / Batterie	LITHIUM - IONEN UN 3481 Zelle / Batterie in Ausrüstungen	BATTERIE mit MEHR als 100 Wh

Place, Date	Signature	Company stamp and Signature
Frankfurt, 21.07.2019	PM	Technaxx Deutschland GmbH & Co. KG Kruppstr. 105 60388 Frankfurt a.M. Fon +49(0)69/90 47 55 2-0 Fax -16