

LITHIUM CELL TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name/Description of cell / model n o. of Product	
Lithium ion / 551240	BT-X59

Manufacturer of cell

Name	Hui Zhou Hao De ENERGY CO.LTD
Address	Floor 5-6, Huiyuan Industrial Park, Yongshi Avenue, Shiwan Town, BOLUO County, Huizhou City, Guangdong Province
Phone	0752-6811498
E-Mail	1219288297@qq.com
Website	

Manufacturer

Name	Technaxx Deutschland GmbH & Co. KG
Address	Kruppstraße 105, 60388 Frankfurt am Main
Phone	+49 [69] 90 47552 0
E-Mail	Zentrale@technaxx.de
Website	http://www.technaxx.de/

Test laboratory of cell

Name	Pony Testing International Group Shenzhen Co.,Ltd
Address	1/F., Building A2, Jun Feng ZhongCheng ZhiZao Innovation Park, HePing Peace Community, FuHai Road, BaoAn District, Shenzhen, Guangdong
Phone	0752-2111979
E-Mail	hzh@ponytest.com
Website	www.ponytest.com

ID-number and date

Unique test report identification number	MOIIPHST23673721
Date of test report	2020-07-06

DESCRIPTION OF CELL (Mark with an "X")

Lithium ion cell	Polymer Li-ion Battery
Lithium metal cell	

Parameters

Mass in gram (g):	4.608
Lithium ion: Indicate watt-hour rating (Wh):	0.814
Lithium metal: Indicate lithium metal content in gram (g):	

Physical description of cell

Lithium Ion

Model numbers

521240

TESTS AND RESULTS

List of tests conducted and results - Mark N/A, pass or fail with an "X"	N/A	Pass	Fail
T1 - Altitude simulation		X	
T2 - Thermal Test		X	
T3 - Vibration		X	
T4 - Shock		X	
T5 - External Short Circuit		X	
T6 - Impact - for cylindrical cells having a diameter of at least 18 mm		X	
T6 - Crush - for prismatic cells, pouch cells, button cells and cylindrical cells having a diameter of less than 18 mm		X	
T7 - Overcharge		X	
T8 - Forced Discharge		X	

ADDITIONAL SUPPLIER INQUIRY

Mark Yes or no with an "X"	Yes	No
Quality management system for manufacturing cells Does the manufacturer of the cell/battery manufacture the products based on a documented quality management system according to transport regulations?	X	
Are the following parameters exceeded? Lithium ion cell: more than 20 Wh Lithium metal cell: more than 1 g Lithium		X

Check point 13 – 15 need to be answered when 12 has been ticked "YES":

Mark Yes or no with an "X"	Yes	No
Does each cell incorporates a safety venting device or is designed to preclude a violent rupture under normal conditions of carriage?		
Is each cell equipped with an effective means of preventing external short circuits?		
Is each battery containing cells or series of cells connected in parallel equipped with effective means as necessary to prevent dangerous reverse current flow (e.g. diodes, fuses, etc.) Not relevant for cells		




Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion cells and lithium polymer cells

State of Charge (SoC) max. 30 %		
---------------------------------	--	--

CELLS INSTALLED IN EQUIPMENT

Check point 17 needs to be answered when the cells are installed in articles: Mark N/A, pass or fail with an "X"	N/A	Pass	Fail
17c) Only button cells enclosed?			
17b) Number of enclosed cells (other than button cells) per equipment			
When the equipment is intentionally active/switched on during transport e.g. data loggers:			
17c) Confirmation that no dangerous amount of heat is emitted from the equipment			
17d) Confirmation that the equipment when transported by air fulfills the defined air transport standards for electromagnetic radiation according to DO-160			

Please mark the correct column with an X

	X	
Single Cell or Battery	Build in Cell/ Battery	Over 100Wh
		

Place, Date	Signature	Company stamp and Signature
Frankfurt, 23.04.2021	