LITHIUM CELL TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

	Name/Description of cell / mo				
Lithium ion		3T-X35 black & gold/silve	er		
		acturer of cell			
Name		Guangxi Zhuoneng New Energy Technology Co., Ltd			
Address	•	Industrial Zone, Qinbei District, Qinzhou City Guangxi Zhuang Autonomous Region,			
Phone	China +86-777-5812222				
E-Mail	renzheng@szznp.com				
Website	www.szznp.com				
VVCDSICC	•	nufacturer			
Name	Technaxx Deutschland GmbH & C				
Address	Kruppstraße 105, 60388 Frankfurt				
Phone	+49 [69] 90 47552 0				
E-Mail	Zentrale@technaxx.de				
Website	http://www.technaxx.de/				
	Test lab	oratory of cell			
Name	Pony Testing International Group	Pony Testing International Group			
Address	Building 1, yard 66, Jindai Road, Z	nongguancun environment	al		
		protection technology demonstration park, Haidian District, Beijing			
Phone	,	010-83055000/82618116			
E-Mail		pony@ponytest.com			
Website	www.ponytest.com				
		ber and date			
	identification number	MPITZZ2C48451	721		
Date of test report		2021-04-09			
	DESCRIPTION OF	CELL (Mark with an"X")			
Lithium ion cell		Х			
Lithium metal cell					
	Pa	rameters			
Mass in gram (g):		42.5			
	ate watt-hour rating (Wh):	7.4			
Litnium metai: ind	licate lithium metal content in gram (g):	escription of cell			
Lithium ion Potts	<u> </u>	escription of cen			
Lithium-ion Batto	zi y				
	Mod	el numbers			
GZNS18650-2000r					
		AND RESULTS	1	1 _	T.
List of tests condu	cted and results		N/A	Pass	Fai

List of tests conducted and results		Pass	Fail
- Mark N/A, pass or fail with an "X"			
T1 - Altitude simulation		Х	
T2 - Thermal Test		Х	
T3 – Vibration		Х	
T4 – Shock		Х	
T5 - External Short Circuit		X	
T6 - Impact - for cylindrical cells having a diameter of at least 18 mm		X	
T6 - Crush - for prismatic cells, pouch cells, button cells and cylindrical cells		X	
having a diameter of less than 18 mm			
T7 – Overcharge	Х		
T8 - Forced Discharge		Х	

ADDITIONAL SUPPLIER INQUIRY

Mark Yes or no with an "X"		No
Quality management system for manufacturing cells		
Does the manufacturer of the cell/battery manufacture the products based on a		
documented quality management system according to transport regulations?		
Are the following parameters exceeded?		Х
Lithium ion cell: more than 20 Wh		
Lithium metal cell: more than 1 g Lithium		

Check point 13 – 15 need to be answered when 12 has been ticked "YES":

Mark Yes or no with an "X"	Yes	No
Does each cell incorporates a safety venting device or is designed		
to preclude a violent rupture under normal conditions of carriage?		
Is each cell equipped with an effective means of preventing external short circuits?		
Is each battery containing cells or series of cells connected in parallel		
equipped with effective means as necessary to prevent dangerous reverse		
current flow (e.g. diodes, fuses, etc.) Not relevant for cells		

Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion cells and lithium polymer cells

State of Charge (SoC) max. 30 %				l
---------------------------------	--	--	--	---

CELLS INSTALLED IN EQUIPMENT

Check point 17 needs to be answered when the cells are installed in articles: Mark N/A, pass or fail with an "X"		Pass	Fail
17c) Only button cells enclosed?			
17b) Number of enclosed cells (other than button cells) per equipment			•
When the equipment is intentionally active/switched on during transport e.g. data logge	rs:		
17c) Confirmation that no dangerous amount of heat is emitted from the equipment			
17d)Confirmation that the equipment when transported by air fulfills the defined air			
transport standards for electromagnetic radiation according to DO-160			

Please mark the correct column wit		
	X	
Single Cell or Battery	Build in Cell/ Battery	Over 100Wh
LITHIUM - METALL UN 3090 UN 3090 Einzel Zelle / Batterie	UN 3481 UN 3481 VIENTINE DE PROPERTIE IN Ausrüstungen	BATTERIE mit MEHR als 100 Wh

Place, Date	Signature	Company stamp and Signature
Frankfurt, 20.04.2021	PM	Technaxx Deutschland GmbH & Co. KG Kruppstr. 105 60388 Frankfurt a.M. Fon +49(0)69/90 47 55 2-0 Fax -16