

Door and window contact TX-86 Accessories for WiFi Smart Alarm Starter Kit TX-84



Sensor-Alarmauslösung ab ~2,5cm Öffnung /
Sensor Alarm Triggering at ~2.5cm Distance



Große Übertragungreichweite zu Sensoren /
Wide Transmission Range to Detectors



Push-Nachricht bei Sabotage /
Push Message at Vandalism



Push-Nachricht bei niedrigem Batteriestand /
Push Message at low Battery Level



Zwei-Wege Kommunikation zwischen Basisstation & Kontakt /
Two Way Communication between Basis Station & Contact

- Sensor alarm triggering at ~2.5cm distance
- Built-in vandalism alarm (case & wall)
- Two-way communication between contact & basis station
- Transmission distance ~200m open space
- Push message at low battery level
- Battery lifespan ~2.5–3 years

Technical specifications:

- Transmission frequency 868MHz
- Transmission power 10dBm
- Distanz detector to magnet: 1mm – 25mm
- Alarm prompt: red LED
- Power supply: 1x CR123A battery 3V
- 128-Bit AES encryption algorithm
- Working conditions: -10°C ~ +50°C / < 95% RH
- Installation: fixed with screws or adhesive tape (indoor only)
- Weight / Dimensions Sensor:
33g (without battery) / (L) 8.3 x (W) 3.8 x (H) 2.0cm
- Weight / Dimensions Magnet: 34g / (L) 8.3 x (W) 2.5 x (H) 2.0cm

Package Contents TX-86:

- Door and window contact TX-86
- 4x screws & 4x dowels & 1x adhesive tape
- 1x CR123A battery



Article-No. 4691

