

MINI Power station TX-205



- 80W AC modified sine wave
- LED light panel and flashlight with 3 modes
- 4 x USB-A (QC3.0), 1 x USB-C PD 18W
- Battery capacity of 74 Wh
- Solar charging compatible (not included)
- Protection against overheating, short-circuit, etc.

Technical specifications:

- Li-Ion battery 74 Wh (20,000 mAh, 3.7 V)
- Power supply (input) 19 V DC, 1.5 A
- Solar panel (input) 15-24 V DC, 1.35 A (max.)
- USB-A output 1 & 3: 5 V DC, 2.4 A Total: 5 V, 4.8 (max.)
- USB-A output 2 & 4 (QC3.0): 5-12 V DC, 2 A, 18 W (max.) Total: 5 V, 3.4 A (max.)
- USB-C output: 5 V DC, 3 A / 9 V DC, 2 A / 12 V DC, 1.5 A / PD 2.0, 18 W (max.)
- DC output: 12-16.8 V DC, 10 A (10.8 A max.)
- AC output: 220 V, 50 Hz, 120 W (max.)
- AC waveform: modified sine wave
- AC nominal power / peak power: 80 W / 120 W
- Charging time approx. 5 hours
- Operating temperature: -10°C to 40°C
- Protected against: Short circuit, overheating, overcharge, overvoltage, undervoltage, overcurrent
- Flashlight: 1 W, 120 lm; 3 functions
- LED panel 90 lm / 120 lm
- Connections: 1 x DC output (DC5521), 4 x USB-A output, 1 x USB-C output, 1 x 230 V output, 1 x DC input (DC35135)
- Dimensions / Weight: 14.5 x 10.5 x 7.7 cm / 1.2 kg

Package Contents:

Technaxx MINI Power Station TX-205,
AC adapter, 12V DC adapter, user manual

Article-No. 5014

