LITHIUM CELL TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

Name/Description of cell / model no. of product	
	e.g. BT-X56

Manufacturer of cell

Name	Huizhou Dinggao Battery Co., Ltd.
Address No.16, 6 South Rode Laohuiling Group, BaiGang Village, Xiaojingkou	
	District, HuiCheng Area, Huizhou, Guangdong Province, China
Phone	+86-13823358834
E-Mail	57163753@qq.com
Website	www.11467.com/qiye/74409392.htm

Manufacturer of the equipment (if the cell is contained in equipment)

Name	Technaxx Deutschland GmbH & Co. KG	
Address Kruppstraße 105, 60388 Frankfurt am Main		
Phone	+49 [69] 90 47552 0	
E-Mail	Zentrale@technaxx.de	
Website	www.technaxx.de	

Test laboratory of cell

Name	Shenzhen LCS Compliance Testing Laboratory., Ltd.
Address	Room 101, 201 Building A and 301 Building C, Juji Industrial Park, Yabianxueiwei, Shajing Street, Baoan District Shenzhen Guangdong China
Phone	+86-075582591330
E-Mail	webmaster@lcs-cert.com
Website	www.lcs-cert.com

ID-number and date

Unique test report identification number	LCS210111110ASA
Date of test report	2021-01-22

DESCRIPTION OF CELL (Mark with an"X")

Lithium ion cell	X
Lithium metal cell	

Parameters

Mass in gram (g):	91.2g
Lithium ion: Indicate watt-hour rating (Wh):	3.7V
Lithium metal: Indicate lithium metal content in	
gram (g):	

Physical description of cell

Li-ion Battery 18650 3.7V 3600mAh	
	-

Model numbers

18650-3600			
------------	--	--	--

TESTS AND RESULTS

List of tests conducted and results	N/A	Pass	Fail
- Mark N/A, pass or fail with an "X"			
T1 - Altitude simulation		X	
T2 - Thermal Test		X	
T3 – Vibration		X	
T4 - Shock		X	
T5 - External Short Circuit		X	
T6 - Impact - for cylindrical cells having a diameter of at least 18		X	
тт			
T6 - Crush - for prismatic cells, pouch cells, button cells and		X	
cylindrical cells			
having a diameter of less than 18 mm			
T7 – Overcharge		X	
T8 - Forced Discharge		X	

Reference to the revised edition of the Manual of Tests and Criteria used and to amendments thereto

ADDITIONAL SUPPLIER INQUIRY

Mark Yes or no with an "X"	Yes	No
Quality management system for manufacturing cells	X	
Does the manufacturer of the cell/battery manufacture the products		
based on a		
documented quality management system according to transport		
regulations?		
Are the following parameters exceeded?	×	
Lithium ion cell: more than 20 Wh		
Lithium metal cell: more than 1 g Lithium		

Check point 13 - 15 need to be answered when 12 has been ticked "YES":

Mark Yes or no with an "X"	Yes	No
Does each cell incorporates a safety venting device or is designed	×	
to preclude a violent rupture under normal conditions of carriage?		
Is each cell equipped with an effective means of preventing external	Х	
short circuits?		
Is each battery containing cells or series of cells connected in parallel	×	
equipped with effective means as necessary to prevent dangerous		
reverse		
current flow (e.g. diodes, fuses, etc.) Not relevant for cells		

Only	, in air trans	port: State	of Charge	(SoC)	for UN	3480	Lithium	ion	cells	and	lithium	polymer	cells

		State of Charge (SoC) max. 30 %	X		ı
--	--	---------------------------------	---	--	---

CELLS INSTALLED IN EQUIPMENT

Check point 17 needs to be answered when the cells are installed in	N/A	Pass	Fail		
articles: Mark N/A, pass or fail with an "X"					
17c) Only button cells enclosed?		X			
17b) Number of enclosed cells (other than button cells) per	17b) Number of enclosed cells (other than button cells) per				
equipment					
When the equipment is intentionally active/switched on during transport e.g. data					
loggers:					
17c) Confirmation that no dangerous amount of heat is emitted		X			
from the equipment					
17d)Confirmation that the equipment when transported by air		X			
fulfills the defined air transport standards for electromagnetic					
radiation according to DO-160					

Place, Date	Title, Surname, First Name	Company stamp and Signature			
Frankfurt am Main, den 23.01.2021	Pekcan, Pascal	Technaxx Deutschland GmbH & Co. KG Kruppstr. 105 60388 Frankfurt a.M. Fon +49(0)69/90 47 55 2-0 · Fax -16			