

LITHIUM BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3

OF MANUAL OF TESTS AND CRITERIA

1. Name/Description of battery
Button Lithium-Ion Battery LIR3048 3.7V 280mAh 1.036Wh
1a. Name/Description of the cells inside the battery

The test summary of the cells inside the battery must either be presented or under checkpoint 9 and 9a it must be confirmed that the UN 38.3 test summary for the cells is available.

2. Manufacturer of battery	
Name	Guangdong Liju New Energy Co. Ltd.
Address	广东力聚新能源有限公司 Guangdong Liju New Energy Co., Ltd.广东省东莞市大岭山镇大岭山拥军路136号1栋802室802, Building1, GuanghuiZhigu, No.136 Yongjun Road, Dalingshan Town, Dongguan City,Guangdong Province,china
Phone	13713968406
Email	13713968406@163.com
Website	www.lijubattery.com

2a. Manufacturer of the equipment (if the battery is contained in equipment)	
Name	
Address	
Phone	
Email	
Website	

3. Test laboratory of battery	
Name	
Address	上海化工院检测有限公司 Shanghai Institute of Chemical Industry Testing Co.,Ltd.中国. 上海.普陀区云岭东路345号,200062No.345 East Yunling Road,Putuo, Shanghai,China 200062
Phone	86-21-31765555
Email	battery@ghs.cn
Website	www.ghs.cn

4. ID-number and date			
Unique test report identification number	1125110042	Date of test report	2025-12-02

DESCRIPTION OF BATTERY

5. Mark the type of battery with an "X"			
X	Lithium ion battery	Lithium metal battery	Lithium hybrid battery

6. Parameters	
Mass in gram (g):	9.59
Lithium ion: Indicate watt-hour rating (Wh):	1.036
Lithium metal: Indicate lithium metal content in gram (g):	
Lithium hybrid: Indicate lithium metal content in gram (g) and watt-hour rating (Wh):	

LITHIUM BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3

OF MANUAL OF TESTS AND CRITERIA

7. Physical description of battery
Appearance: button

8. Model numbers
LIR3048

TESTS AND RESULTS

9. List of tests conducted and results - Mark N/A, pass or fail with an "X"	N/A	Pass	Fail
T1 - Altitude simulation		x	
T2 - Thermal Test		x	
T3 - Vibration		x	
T4 - Shock		x	
T5 - External Short Circuit		x	
T6 - Impact - for cylindrical cells having a diameter of at least 18 mm See check point 1a and 9a.	x		
T6 - Crush - for prismatic cells, pouch cells, button cells and cylindrical cells having a diameter of less than 18 mm. See check point 1a and 9a.		x	
T7 - Overcharge	x		
T8 - Forced Discharge, only valid for cells. See check point 1a and 9a.		x	
9 List the tests conducted and results-T9 Text			
9 List the tests conducted and results-T10 Text			

9a. UN 38.3 Test Confirmation for the Cells inside the battery When no separate document for the cells is provided, this confirms that the cells inside the battery (see checkpoint 1.a.) have successfully passed the UN 38.3 test. In this case under checkpoint 9 the T.6 and T.8 must be marked as „passed“ and here under 9.a. „Cell UN 38.3 Test confirmed“ needs to be ticked.	Cell UN 38.3 Test confirmed		Cell UN 38.3 Test NOT confirmed	
---	------------------------------------	--	--	--

10. Reference to assembled battery testing requirements			
Altitude simulation, Thermal test, Vibration, Shock, External sort circuit, Impact, Overcharge, Forced discharge		N/A	

11. Reference to the revised edition of the Manual of Tests and Criteria used and to amendments thereto			

ADDITIONAL SUPPLIER INQUIRY

12. Quality management system for manufacturing batteries Does the manufacturer of the battery manufacture the products based on a documented quality management system according to transport regulations?	yes	x	no	
---	-----	---	----	--

13. Are the following parameters exceeded? Lithium ion battery: more than 100 Wh Lithium metal battery: more than 2 g Lithium Lithium hybrid Battery: more than 1,5 g Lithium and/or more than 10 Wh	yes		no	x
--	-----	--	----	---

LITHIUM BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3

OF MANUAL OF TESTS AND CRITERIA

Check point 14 – 16 need to be answered when 13 has been ticked “YES”:					
14. Does each battery incorporates a safety venting device or is designed to preclude a violent rupture under normal conditions of carriage?			Yes		no
15. Is each battery equipped with an effective means of preventing external short circuits?			Yes		No
16. Is each battery containing cells or series of cells connected in parallel equipped with effective means as necessary to prevent dangerous reverse current flow (e.g. diodes, fuses, etc.)?	N/A		Yes		No

17. Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion batteries and lithium polymer batteries					
State of Charge (SoC) max. 30 %	N/A	x	Yes		No

BATTERIES INSTALLED IN EQUIPMENT

18. Check point 18 needs to be answered when the batteries are installed in articles:					
18.a) Only button cells enclosed?			Yes	x	No
18.b) Number of enclosed batteries per equipment					1
When the equipment is intentionally active/switched on during transport e.g. data loggers:					
18.c) Confirmation that no dangerous amount of heat is emitted from the equipment	N/A	x	Yes		No
18.d) Confirmation that the equipment when transported by air fulfills the defined air transport standards for electromagnetic radiation according to DO-160	N/A	x	Yes		No

19. Place, Date	20. Title, Surname, First name and signature	21. Company stamp
Schöneck, 21.01.2026	 CEO, Pekcan, Pascal	Technaxx Deutschland GmbH & Co.KG Konrad-Zuse-Ring 16-18 61137 Schöneck-Kilianstädten Fon +49 (0)6187 / 200 92-0 • Fax -16