LITHIUM CELL TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

	Name/Description of cell / me			
		e.g. TX-277		
		acturer of cell		
Name	Shenzhen Yuebada Technology Co., Ltd.			
Address	D401, No.2, Honglianying Workshop No. 286 Sili Road, Xinlan Commu			
	Guanlan Street, Longhua Distr	ct, Shenzhen, Guangdong, P.R. China		
Phone	+86 755 33952944	+86 755 33952944		
E-Mail	1766817695@qq.com			
Website				
	Ma	nufacturer		
Name	Technaxx Deutschland GmbH & C	o. KG		
Address	Konrad-Zuse-Ring 16-18, 61137 S	chöneck		
Phone	+49 6187 20092 0			
E-Mail	Zentrale@technaxx.de			
Website	http://www.technaxx.de/			
	· ·	oratory of cell		
Name	Shenzhen NCT Testing Technolog			
Address	A101, 1/F., &2F., B2, Fuqiao 6 ^t	h Area, Xintian, Fuhai Street, Bao'an District		
	Shenzhen Guangdong China			
Phone	+86 755 27790922	+86 755 27790922		
E-Mail	sales@nct-testing.com	sales@nct-testing.com		
Website	www.ncttesting.cn			
	ID-nur	nber and date		
Unique test report id	dentification number	NCT240221245XM1-1		
Date of test report		2024-05-31		
	DESCRIPTION OF	CELL (Mark with an"X")		
Lithium ion cell		X		
Lithium metal cell				
	Pa	rameters		
Mass in gram (g):		29.9g		
Lithium ion: Indicate watt-hour rating (Wh): Lithium metal: Indicate lithium metal content in gram (g):		6.66Wh		
Litinum metal: maic	ate numum metai content in gram (g):			
	Physical c	escription of cell		
		el numbers		

TESTS AND RESULTS

List of tests conducted and results		Pass	Fail
- Mark N/A, pass or fail with an "X"			
T1 - Altitude simulation		Х	
T2 - Thermal Test		Х	
T3 – Vibration		Х	
T4 – Shock		Х	
T5 - External Short Circuit		Х	
T6 - Impact - for cylindrical cells having a diameter of at least 18 mm		Х	
T6 - Crush - for prismatic cells, pouch cells, button cells and cylindrical cells		Х	
having a diameter of less than 18 mm			
T7 – Overcharge		Х	
T8 - Forced Discharge		Х	

Reference to the revised edition of the Manual of Tests and Criteria used and to amendments thereto

ADDITIONAL SUPPLIER INQUIRY

Mark Yes or no with an "X"		No
Quality management system for manufacturing cells		
Does the manufacturer of the cell/battery manufacture the products based on a		
documented quality management system according to transport regulations?		
Are the following parameters exceeded?		
Lithium ion cell: more than 20 Wh		
Lithium metal cell: more than 1 g Lithium		

Check point 13 – 15 need to be answered when 12 has been ticked "YES":

Mark Yes or no with an "X"	Yes	No
Does each cell incorporates a safety venting device or is designed		
to preclude a violent rupture under normal conditions of carriage?		
Is each cell equipped with an effective means of preventing external short circuits?	X	
Is each battery containing cells or series of cells connected in parallel		
equipped with effective means as necessary to prevent dangerous reverse		
current flow (e.g. diodes, fuses, etc.) Not relevant for cells		

Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion cells and lithium polymer cells

State of Charge (SoC) max. 30 %	X		
---------------------------------	---	--	--

CELLS INSTALLED IN EQUIPMENT

Check point 17 needs to be answered when the cells are installed in articles: Mark		Pass	Fail
N/A, pass or fail with an "X"			
17c) Only button cells enclosed?		Х	
17b) Number of enclosed cells (other than button cells) per equipment			
When the equipment is intentionally active/switched on during transport e.g. data loggers:			
17c) Confirmation that no dangerous amount of heat is emitted from the equipment		Х	
17d)Confirmation that the equipment when transported by air fulfills the defined air		Х	
transport standards for electromagnetic radiation according to DO-160			

Please markt he correct column with an X		
Single Cell or Battery	Build in Cell/ Battery	Over 100Wh







Place, Date	Signature	Company stamp and Signature
2024-07-09		Technaxx Deutschland
		GmbH & Co.KG
	1/W	Konrad-Zuse-Ring 16-18
	V	61137 Schöneck-Kilianstädten
		Fon +49 (0)6187 / 200 92-0 • Fax -16