LITHIUM CELL TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

	Name/Description of cell / models	o. of Product			
Lithium polymer battery TX-SW6HR					
	Manufacture	er of cell			
Name	Shenzhen Theurgy Technology Co.	Shenzhen Theurgy Technology Co.,Ltd			
Address	5 floor, NO.8, First Indurstrial Zone	5 floor, NO.8, First Indurstrial Zone, Liaokeng, Shiyan town,Baoan			
	district,Shenzhen	district,Shenzhen			
Phone	0755-29163899	0755-29163899			
E-Mail	wanghui@mitacbattery.com	wanghui@mitacbattery.com			
Website	bsite				
	Manufac	turer			
Name	Technaxx Deutschland GmbH & Co. KO	Technaxx Deutschland GmbH & Co. KG			
Address	Kruppstraße 105, 60388 Frankfurt am	Kruppstraße 105, 60388 Frankfurt am Main			
Phone	+49 [69] 90 47552 0				
E-Mail	Zentrale@technaxx.de				
Website		http://www.technaxx.de/			
	Test laborato	ry of cell			
Name	Pony Testing International Group				
Address					
Phone	400-819-5688				
E-Mail					
Website	www.ponytest.com				
	ID-number a	nd date			
Unique test report identification number		MNIDILEM89961	721		
Date of test report		2020-03-20			
	DESCRIPTION OF CELg	Mark with an"X")			
Lithium ion cell		Х			
Lithium metal cell					
	Parame	ters			
Mass in gram (g):		3.7			
Lithium ion: Indicate watt-hour rating (Wh):		0.666			
Lithium metal: Indicate lithium metal content in gram (g):					
	Physical descrip	tion of cell			
Prismatic ISIP					
	Model nui	mbers			
352224					
	TESTS AND F	RESULTS			
List of tests conducted and results N/A Pass			Fail		
- Mark N/A, pass or	fail with an "X"				
			+		

List of tests conducted and results		Pass	Fail
- Mark N/A, pass or fail with an "X"			
T1 - Altitude simulation		Х	
T2 - Thermal Test		X	
T3 – Vibration		X	
T4 – Shock		X	
T5 - External Short Circuit		X	
T6 - Impact - for cylindrical cells having a diameter of at least 18 mm		X	
T6 - Crush - for prismatic cells, pouch cells, button cells and cylindrical cells		X	
having a diameter of less than 18 mm			
T7 – Overcharge		X	
T8 - Forced Discharge		Х	

ADDITIONAL SUPPLIER INQUIRY

Mark Yes or no with an "X"		No
Quality management system for manufacturing cells		
Does the manufacturer of the cell/battery manufacture the products based on a		
documented quality management system according to transport regulations?		
Are the following parameters exceeded?		Х
Lithium ion cell: more than 20 Wh		
Lithium metal cell: more than 1 g Lithium		

Check point 13 – 15 need to be answered when 12 has been ticked "YES":

Mark Yes or no with an "X"	Yes	No
Does each cell incorporates a safety venting device or is designed		
to preclude a violent rupture under normal conditions of carriage?		
Is each cell equipped with an effective means of preventing external short circuits?	Х	
Is each battery containing cells or series of cells connected in parallel		
equipped with effective means as necessary to prevent dangerous reverse		
current flow (e.g. diodes, fuses, etc.) Not relevant for cells		

Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion cells and lithium polymer cells

State of Charge (SoC) max. 30 %

CELLS INSTALLED IN EQUIPMENT

Check point 17 needs to be answered when the cells are installed in articles: Mark	N/A	Pass	Fail
N/A, pass or fail with an "X"			
17c) Only button cells enclosed?		Х	
17b) Number of enclosed cells (other than button cells) per equipment			
When the equipment is intentionally active/switched on during transport e.g. data logge	rs:		
17c) Confirmation that no dangerous amount of heat is emitted from the equipment		Х	
17d)Confirmation that the equipment when transported by air fulfills the defined air		Х	
transport standards for electromagnetic radiation according to DO-160			

	Х	
Single Cell or Battery	Build in Cell/ Battery	Over 100Wh
LITHIUM - METALL UN 3090 UN 3090 Einzel Zelle / Batterie	LITHIUM - IONEN UN 3481 Zelle / Batterie in Ausrüstungen	BATTERIE mit MEHR als 100 Wh

Date	Pascal Pekcan CEO	Company stamp
20.09.2020	PM	Technaxx Deutschland GmbH & Co. KG Kruppstr. 105 60388 Frankfurt a.M. Fon +49(0)69/90 47 55 2-0 · Fax-16