

Wireless Video Door Phone TX-59+

Wireless outdoor camera for the entrance door with 7" TFT LCD indoor monitor



7" TFT LCD Monitor	640x480 Video Auflösung/ 640x480 Video Resolution	IP55 Kameraschutzklasse/ IP55 Camera Protection	120° Weitwinkel/ 120° Wide Angle	Bewegungserkennung ~3m/ Motion Detection ~3m	2x IR LED	Infrarot Nachsicht ~1,5m/ Infrared night vision ~1.5m
Türöffner/ Door opener	Mikrofon/ Microphone	Lautsprecher/ Loudspeaker	1-Weg/2-Wege-Gegensprechfunktion/ 1-Way/2-Way Voice Function	Video- & Fotoaufnahmen/ Video & Photo Recording	Kamera ist verstellbar / Camera is adjustable	

- Show up to 2 outdoor cameras on 1 indoor monitor
- Show 1 outdoor camera on up to 3 indoor monitors
- Supports communication between 2 or 3 indoor monitors
- Intercom function via built-in microphone and speaker
- Video & Photo recording function
- IP55 camera protection class (against waterjet & dust)
- Motion Detection ~3m
- Infrared night vision ~1.5m with 2x IR LED
- Wireless transmission ~200m open areas
- Camera is adjustable
- Doorbell function & connection with electric door opener possible
- Videos saved on MicroSD card up to 32GB
- Easy handling and setting

Technical Specifications outdoor CAMERA:

- 300000 pixels & 120° wide-angle
- Replaceable rechargeable (~6.5 hours) lithium battery 3400mAh 12.5Wh 3,7V
- Playing time ~6 hours continuously, Standby ~60 days
- Current consumption 400mA & external power supply 9V~16V DC/AC
- Built-in microphone and speaker
- Operating temperature -10°C up to +40°C
- Outdoor wall mount (incl. mounting material)
- Weight / Dimensions: 138g / (L) 13.4 x (W) 7.4 x (H) 3.1cm

Camera & Monitor:

Transmitting frequency: 2.4GHz / Maximum radiated output power: 100mW

Technical Specifications indoor MONITOR:

- 7" TFT LCD indoor monitor with 640x480 video resolution
- Replaceable rechargeable (~6.5 hours) lithium battery 4000mAh 14.8Wh 3,7V
- Current consumption 400mA & external power supply DC 9V/2A
- 1-way or 2-way intercom function
- Loop recording function on MicroSD card up to 32GB
- Control buttons on the front for easy operation
- Control buttons sideways for different adjustments
- Possible to connect an electrical door opener 6V-12V
- Built-in microphone and speaker
- Operating temperature 0°C up to +40°C
- Stand for plain surfaces
- Indoor wall mount (incl. mounting material)
- Weight / Dimensions: 387g / (L) 20.0 x (W) 15.0 x (H) 2.7cm



Package Contents:

1x Outdoor camera (wireless transmission), 1x 7" indoor monitor (wireless reception), 2x DC 9V Charging adapter, 1x DC Cable for outdoor camera, 2x Lithium-ion battery (camera & monitor), 2x screws M3, 1x Waterproof case + 3x screws, 1x Wall bracket + 4x screws, User Manual

Available seperately:

Additional Camera for TX-59+

EAN 4260358123066, Article No. 4771

Replaceable battery for the camera

Lithium ion battery 3400mAh 12,5Wh 3,7V
EAN 4260358121482, Article No. 4653

Additional Monitor for TX-59+

EAN 4260358123073, Article No. 4772

Replaceable battery for the monitor

Lithium ion battery 4000mAh 14.8Wh 3.7V
EAN 4260358121550, Article No. 4630

Article-No. 4770

