LITHIUM CELL TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

	Name/Description of cell / r				
EE402030 Lithium ion battery TX-185					
	Manu	facturer of cell			
Name	Shenzhen Erer Technology Co.,Ltd				
Address	605, No.78-1, Xintang Road, Xintian Community, Fuhai Street, Baoan				
	District, Shenzhen, China				
Phone	+86-755-23227646				
E-Mail	545525380@qq.com				
Website					
	Ma	nufacturer			
Name	Technaxx Deutschland GmbH	1 & Co. KG			
Address	Konrad-Zuse-Ring 16-18, 611	.37 Schöneck			
Phone	+49 [69] 90 47552 0				
E-Mail	Zentrale@technaxx.de				
Website	http://www.technaxx.de/				
	Test la	poratory of cell			
Name	CMC Testing International (S	henzhen) Co., Ltd			
Address	101, Building B, Kaihuimao Industrial Park, Liyuan Road, Heping				
	Community, Fuhai Street, Baoan District, Shenzehen, Guangdong, China			ıa	
Phone	+86 400-1668-320				
E-Mail	info@cmczj-lab.com				
Website	www.cmczj-lab.com				
	ID-nur	nber and date			
Unique test report identification number CMC220512029					
Date of test report		2022-05-27	2022-05-27		
	DESCRIPTION OF	CELL (Mark with an"X")			
Lithium ion cell		X			
Lithium metal cell					
	Pa	arameters			
Mass in gram (g):		4.32			
Lithium ion: Indicate watt-hour rating (Wh):		0.74			
Lithium metal: Indicate lithium metal content in gram (g):					
		•			
	Physical o	description of cell			
Single cell lithium ion ba	ttery				
	Mod	del numbers			
EE402030					
	TECTC	AND RESULTS			
List of tests conducted a		AND NEGOTIO	N/A	Pass	Fa

List of tests conducted and results		Pass	Fail
- Mark N/A, pass or fail with an "X"			
T1 - Altitude simulation		Х	
T2 - Thermal Test		X	
T3 – Vibration		X	
T4 – Shock		X	
T5 - External Short Circuit		X	
T6 - Impact - for cylindrical cells having a diameter of at least 18 mm	Х		
T6 - Crush - for prismatic cells, pouch cells, button cells and cylindrical cells		X	
having a diameter of less than 18 mm			
T7 – Overcharge		X	
T8 - Forced Discharge		Х	

ADDITIONAL SUPPLIER INQUIRY

Mark Yes or no with an "X"		No
Quality management system for manufacturing cells		
Does the manufacturer of the cell/battery manufacture the products based on a		
documented quality management system according to transport regulations?		
Are the following parameters exceeded?		Х
Lithium ion cell: more than 20 Wh		
Lithium metal cell: more than 1 g Lithium		

Check point 13 – 15 need to be answered when 12 has been ticked "YES":

Mark Yes or no with an "X"	Yes	No
Does each cell incorporates a safety venting device or is designed		
to preclude a violent rupture under normal conditions of carriage?		
Is each cell equipped with an effective means of preventing external short circuits?		
Is each battery containing cells or series of cells connected in parallel		
equipped with effective means as necessary to prevent dangerous reverse		
current flow (e.g. diodes, fuses, etc.) Not relevant for cells		

Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion cells and lithium polymer cells

State of Charge (SoC) max. 30 %

CELLS INSTALLED IN EQUIPMENT

Check point 17 needs to be answered when the cells are installed in articles: Mark	N/A	Pass	Fail
N/A, pass or fail with an "X"			
17c) Only button cells enclosed?			
17b) Number of enclosed cells (other than button cells) per equipment			
When the equipment is intentionally active/switched on during transport e.g. data logge	ers:		
17c) Confirmation that no dangerous amount of heat is emitted from the equipment			
17d)Confirmation that the equipment when transported by air fulfills the defined air			
transport standards for electromagnetic radiation according to DO-160			

	X	
Single Cell or Battery	Build in Cell/ Battery	Over 100Wh
LITHIUM - METALL UN 3090 UN 3090 Einzel Zelle / Batterie	LITHIUM - IONEN UN 3481 Zelle / Batterie in Ausrüstungen	BATTERIE mit MEHR als 100 Wh

Place, Date	Signature	Company stamp and Signature
Schöneck, 31.05.2021		Technaxx Deutschland
		GmbH & Co.KG
	WW .	Konrad-Zuse-Ring 16-18
	V	61137 Schöneck-Kilianstädten
		Fon +49 (0)6187 / 200 92-0 • Fax -16