LITHIUM BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3
OF MANUAL OF TESTS AND CRITERIA

1. Name/Description of battery
Button lithium-ion cell LIR3048, 3.7 V, 280 mAh, 1.036 Wh (rechargeable Li-ion cell, brand marking "liju")
1a. Name/Description of the cells inside the battery
Not applicable – single-cell battery (button cell LIR3048); the battery consists of one cell only. Cell UN 38.3 test confirmed, see 9a.

The test summary of the cells inside the battery must either be presented or under checkpoint 9 and 9a it must be confirmed that the UN 38.3 test summary for the cells is available.

2. Manufacturer of battery	
Name	Guangdong Liju New Energy Co., Ltd
Address	802, Building 1, Guanghui Zhigu, No.136 Yongjun Road, Dalingshan Town, Dongguan City, Guangdong Province, China
Phone	+86 13713968406
Email	13713968406@163.com
Website	www.lijubattery.com

2a. Manufacturer of the equipment (if the battery is contained in equipment)	
Name	Technaxx Deutschland GmbH & Co. KG
Address	Konrad-Zuse-Ring 16-18, 61137 Schöneck, Germany
Phone	+49 6187 200920
Email	gpsr@technaxx.de
Website	www.technaxx.de

3. Test laboratory of battery	
Name	Shanghai Institute of Chemical Industry Testing Co., Ltd. (SICT)
Address	No.345 East Yunling Road, Putuo, Shanghai 200062, China
Phone	+86 21-31765555
Email	battery@ghs.cn
Website	www.ghs.cn

4. ID-number and date			
Unique test report identification number	**1125110042**	Date of test report	**2025-12-02**

DESCRIPTION OF BATTERY

5. Mark the type of battery with an "X"					
X	Lithium ion battery		Lithium metal battery		Lithium hybrid battery

6. Parameters	
Mass in gram (g):	9.59
Lithium ion: Indicate watt-hour rating (Wh):	1.036
Lithium metal: Indicate lithium metal content in gram (g):	N/A
Lithium hybrid: Indicate lithium metal content in gram (g) and watt-hour rating (Wh):	N/A

LITHIUM BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3
OF MANUAL OF TESTS AND CRITERIA

7. Physical description of battery
Appearance: button/coin cell, silvery metal shell, Ø 30.2 mm × 6.0 mm

8. Model numbers
LIR3048

TESTS AND RESULTS

9. List of tests conducted and results - Mark N/A, pass or fail with an " **X**"	N/A	Pass	Fail
T1 - Altitude simulation		**X**	
T2 - Thermal Test		**X**	
T3 – Vibration		**X**	
T4 – Shock		**X**	
T5 - External Short Circuit		**X**	
T6 - Impact - for cylindrical cells having a diameter of at least 18 mm See check point 1a and 9a.	**X**		
T6 - Crush - for prismatic cells, pouch cells, button cells and cylindrical cells having a diameter of less than 18 mm. See check point 1a and 9a.		**X**	
T7 – Overcharge	**X**		
T8 - Forced Discharge, only valid for cells. See check point 1a and 9a.		**X**	
9 List the tests conducted and results-T9 Text			
9 List the tests conducted and results-T10 Text			

9a. UN 38.3 Test Confirmation for the Cells inside the battery When no separate document for the cells is provided, this confirms that the cells inside the battery (see checkpoint 1.a.) have successfully passed the UN 38.3 test. In this case under checkpoint 9 the T.6 and T.8 must be marked as „passed" and here under 9.a. „Cell UN 38.3 Test confirmed" needs to be ticked.	**Cell UN 38.3 Test confirmed**	**X**	**Cell UN 38.3 Test NOT confirmed**	

10. Reference to assembled battery testing requirements			
	Altitude simulation, Thermal test, Vibration, Shock, External sort circuit, Impact, Overcharge, Forced discharge	**N/A**	**X**

11. Reference to the revised edition of the Manual of Tests and Criteria used and to amendments thereto	
	UN Manual of Tests and Criteria, 8th revised edition (ST/SG/AC.10/11/Rev.8), Part III, Section 38.3

ADDITIONAL SUPPLIER INQUIRY

12. Quality management system for manufacturing batteries Does the manufacturer of the battery manufacture the products based on a documented quality management system according to transport regulations?	yes	**X**	**no**	

13. Are the following parameters exceeded? Lithium ion battery: more than 100 Wh Lithium metal battery: more than 2 g Lithium Lithium hybrid Battery: more than 1,5 g Lithium and/or more than 10 Wh	yes		**no**	**X**

LITHIUM BATTERY TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3
OF MANUAL OF TESTS AND CRITERIA

Check point 14 – 16 need to be answered when 13 has been ticked "YES":						
14. Does each battery incorporates a safety venting device or is designed to preclude a violent rupture under normal conditions of carriage?			**Yes**		**no**	
15. Is each battery equipped with an effective means of preventing external short circuits?			**Yes**		**No**	
16. Is each battery containing cells or series of cells connected in parallel equipped with effective means as necessary to prevent dangerous reverse current flow (e.g. diodes, fuses, etc.)?	**N/A**		**Yes**		**No**	

17. Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion batteries and lithium polymer batteries						
State of Charge (SoC) max. 30 %	**N/A**	**X**	**Yes**		**No**	

BATTERIES INSTALLED IN EQUIPMENT

18. Check point 18 needs to be answered when the batteries are installed in articles:						
18.a) Only button cells enclosed?			**Yes**		**No**	
18.b) Number of enclosed batteries per equipment						N/A
When the equipment is intentionally active/switched on during transport e.g. data loggers:						
18.c) Confirmation that no dangerous amount of heat is emitted from the equipment	**N/A**		**Yes**		**No**	
18.d) Confirmation that the equipment when transported by air fulfills the defined air transport standards for electromagnetic radiation according to DO-160	**N/A**		**Yes**		**No**	

19. Place, Date	**20. Title, Surname, First name and signature**	**21. Company stamp**
Schöneck, 2026-08-03	**CEO Pekcan Pascal** 	Technaxx Deutschland GmbH & Co.KG Konrad-Zuse-Ring 16-18 61137 Schöneck-Kilianstädten Fon +49 (0)6187 / 200 92-0 • Fax -16