LITHIUM CELL TEST SUMMARY AND SUPPLIER INQUIRY

IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

604220	Name/Description of cell / mode				
601230	<u>I</u>	112 urer of cell			
Name	1				
Address	ShenZhen FuYouMing Electronics Co.,LTD. Room 306, No. 21-2, Xinshiqiao South lane, Guihua Community, Guanlan				
Audress	Street, Longhua, Shenzhen			all	
Phone	07555-23766037				
E-Mail	1255457255@qq.com				
Website	https://xin.baidu.com/detail/compinfo?pid=xlTM-				
Website	TogKuTwMKV4UwmmutqyTqsc*0kWvgmd&from=ps&fl=1&castk=LTE%3D			63D	
		acturer	1000	in LiL	000
Name	Technaxx Deutschland GmbH & C				
Address		Konrad-Zuse-Ring 16-18, 61137 Schöneck			
Phone	+49 6187 20092 0				
E-Mail	Zentrale@technaxx.de				
Website	http://www.technaxx.de/				
***************************************	Test labora	tory of cell			
Name					
Address	, ,	Shenzhen LCS Compliance Testing Laboratory Ltd			
Address	_	Room 101, 201 Building A and 301 Building C, Juji Industrial Park,			nina
Phone	+(86) 0755-8259 1330	Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, Guangdong, China			
E-Mail	webmaster@lcs-cert.com				
Website	http://www.lcs-cert.com				
VVCDSICC		r and date			
Unique test report	identification number		 SΔ100		
Date of test report					
	DESCRIPTION OF CEL				
Lithium ion cell		X			
Lithium metal cell					
	Paran	neters			
Mass in gram (g):		3.9			
		0.666			
	icate lithium metal content in gram (g):	0.000			
	Physical desc	ription of cell			
Polymer Lithium					
1 Olymer Element	Model r	numbers			
402030					
102000					
	TESTS ANI	O RESULTS			
List of tests condu		, KESOETS	N/A	Pass	Fail
- Mark N/A, pass of			14/7	1 433	
T1 - Altitude simula				Х	
T2 - Thermal Test				X	
T3 – Vibration				Х	
T4 – Shock				Х	İ
T5 - External Short	Circuit			Х	
	lindrical cells having a diameter of at least 18			Х	
·	smatic cells, pouch cells, button cells and cylin	drical cells			
having a diameter	of less than 18 mm				

T7 – Overcharge T8 - Forced Discharge

ADDITIONAL SUPPLIER INQUIRY

Mark Yes or no with an "X"	Yes	No
Quality management system for manufacturing cells		
Does the manufacturer of the cell/battery manufacture the products based on a		
documented quality management system according to transport regulations?		
Are the following parameters exceeded?		Х
Lithium ion cell: more than 20 Wh		
Lithium metal cell: more than 1 g Lithium		

Check point 13 – 15 need to be answered when 12 has been ticked "YES":

Mark Yes or no with an "X"	Yes	No
Does each cell incorporates a safety venting device or is designed		
to preclude a violent rupture under normal conditions of carriage?		
Is each cell equipped with an effective means of preventing external short circuits?		
Is each battery containing cells or series of cells connected in parallel		
equipped with effective means as necessary to prevent dangerous reverse		
current flow (e.g. diodes, fuses, etc.) Not relevant for cells		

Only in air transport: State of Charge (SoC) for UN 3480 Lithium ion cells and lithium polymer cells

State of Charge (SoC) max. 30 %

CELLS INSTALLED IN EQUIPMENT

Check point 17 needs to be answered when the cells are installed in articles: Mark N/A, pass or fail with an "X"	N/A	Pass	Fail
17c) Only button cells enclosed?	X		
17b) Number of enclosed cells (other than button cells) per equipment			1
When the equipment is intentionally active/switched on during transport e.g. data logge	rs:		
17c) Confirmation that no dangerous amount of heat is emitted from the equipment	Х		
17d)Confirmation that the equipment when transported by air fulfills the defined air X			
transport standards for electromagnetic radiation according to DO-160			

	X	
Single Cell or Battery	Build in Cell/ Battery	Over 100Wh
LITHIUM - METALL UN 3090 UN 3090 Einzel Zelle / Batterie	UN 3481 Zelle / Batterie in Ausrüstungen	BATTERIE mit MEHR als 100 Wh

Signature	Company stamp and Signature	
0	Technaxx Deutschland	
	GmbH & Co.KG	
W//W	Konrad-Zuse-Ring 16-18	
V	61137 Schöneck-Kilianstädten Fon +49 (0)6187 / 200 92-0 • Fax -16	
	Signature	